

DATA SHEET MBUS-REP

Version 1 Page 1/2

1. Product

- MBUS-REP125, Order Nr. 500414
- MBUS-REP250, Order Nr. 500417
- MBUS-REP500, Order Nr. 500402



2. Application

Repeater as signal amplifier in an M-Bus network

3. Interfaces

M-Bus Master

Compliant to EN 13757-2 (all M-Bus meters are compatible), max. number of unit loads (UL):

- 125 (MBUS-REP125, Order Nr. 500414)
- 250 (MBUS-REP250, Order Nr. 500417)
- 500 (MBUS-REP500, Order Nr. 500402)

Baud rate: max. 9600 bps, screw terminals

M-Bus Slave

Compliant to EN 13757-2, baud rate: max. 9600 bps, current consumption approx. 3 mA (2 UL), screw terminals

Galvanic isolation

M-Bus master and M-Bus slave are galvanically isolated from each other: 1 kV $\,$

4. LED indicators

 $3~\mbox{LEDs}$ signalling sending, receiving and collision/overload on the M-Bus

5. General properties

- Dimensions: 54 \times 90 \times 60 mm (W \times H \times D), 3 modules wide
- Installation: DIN rail 35 mm (IEC 60715), arbitrary orientation
- Mass: 130 g

6. Power supply

- 12..36 VDC, screw terminals
- Power consumption: <1 W (idle state), max. 40 W
- Peak inrush-current: approx. 4 A

7. Environmental conditions

- Operation: 0..50°C (daily average)
- Transport and storage: -20..70°C (short-time)
- Air humidity: 0..95 %, non-condensing

8. Conformity and safety

- 2014/30/EU EMC Directive
- 2011/65/EU RoHS Directive (incl. amendment 2015/863)
- 1907/2006/EC REACH Regulation (Annex XVII April 28 2020)
- Overvoltage protection (transient)
- Protection class III (IEC 61140)
- Degree of protection IP20 (IEC 60529)

9. Scope of delivery

- MBUS-REP125 (Order Nr. 500414) resp. MBUS-REP250 (Order Nr. 500417) resp. MBUS-REP500 (Order Nr. 500402)
- Quick Start Guide (print, in the packaging)
- Individual packaging with solvimus logo
- Dimensions: $108 \times 67 \times 62 \text{ mm} (W \times H \times D)$



DATA SHEET MBUS-REP

Version 1 Page 2/2

10. Contact

solvimus GmbH Ratsteichstr. 5 98693 Ilmenau Germany Phone: +49 3677 7613060 E-Mail: info@solvimus.de www.solvimus.de

Sales:

Phone: +49 3677 7613066 E-Mail: sales@solvimus.de

Support:

Phone: +49 3677 7613065 E-Mail: support@solvimus.de

Further contacts can be found on our website at: https://www.solvimus.de/en/company/solvimus/

A comprehensive description of the device is provided in the manual that can be downloaded free of charge and without registration from our homepage:

https://www.solvimus.de/en/products/downloads-2/.

Our Quick Start Guide is also available upon request.

The solvimus GmbH works according to the principle of continuous improvement. The information given in this document is subject to change without prior notice and is provided without assertion, warranty or guarantee, including as to accuracy, completeness or fitness for a particular purpose. The statements in this document are not to be construed as a guarantee or assertion. This document is protected under copyright law.