



SOLVIMUS

METERING SOLUTIONS


DATA SHEET MBUS-GEWM

Version 1

Page 1/2

1. Product

MBUS-GEWM, Art. No. 500364



2. Application

Gateway for readout of meters and data transmission to distant data management systems (PLC, SCADA) via Ethernet in Modbus TCP format

3. Interfaces

wM-Bus

Compliant to EN 13757-4/-3/-7 and OMS (modes: S, T, C, C/T), SMA connector for external antenna, frequency: 868 MHz, Listen mode (automatic creation of meters), transparent mode, handling of keys, decryption of meters

Ethernet

Compliant to IEEE 802.3, 10/100-Base-TX, RJ45 connector incl. status LEDs, Auto-MDIX

Modbus

Readout of meters via Modbus TCP, compliant to IEC 61158, using the Ethernet interface

4. LED indicators

2 status LEDs for status and activity

5. Software functions

The user interface of the software is available only in English.

As indicated for the firmware in the manual, update of the firmware via Ethernet incl. integrity check and authentication

Configuration

- Complete configuration via browser: HTTP and HTTPS
- Creation of the meter list
- Mass deployment with Netdiscover via HTTP and HTTPS
- Usage of OBIS codes
- Integrated OpenVPN client
- Extensive management of user access rights
- Export and import of the configuration including certificate and key files
- Update via the web page or Netdiscover
- Print page for error analysis and documentation
- Extensive logging function

Data transmission to the server:

- Modbus TCP

6. Processing unit

The processing unit is a microprocessor system:

- CPU: ARM9 architecture, 454 MHz clock frequency
- Memory: 128 MB RAM, 4 GB internal eMMC Flash
- Operating system: Linux
- Integrated RTC: backed-up for up to 7 days

7. General properties

- Dimensions: 35 x 90 x 59 mm (W x H x D, without antenna socket), 2 modules wide



DATA SHEET MBUS-GEWM

Version 1

Page 2/2

- Installation: DIN rail 35 mm (IEC 60715), arbitrary orientation
- Mass: 85 g

8. Power supply

- 12..36 VDC, screw terminals
- Power consumption: 2W (idle state), max. 5 W
- Peak inrush-current: approx. 3 A

9. Environmental conditions

- Operation: 0..50 °C (daily average), -20..70 °C (short-time)
- Air humidity: 0..95 %, non-condensing

10. Conformity and safety

- 2014/53/EU Radio Equipment Directive
- 2011/65/EU RoHS Directive (incl. amendment 2015/863)
- Overvoltage protection (transient)
- Protection class III (IEC 61140)
- Degree of protection IP30 (IEC 60529)

11. Scope of delivery

- MBUS-GEWM
- 1 antenna for wM-Bus
- Quick Start Guide (print, in the packaging)
- Individual packaging

12. Contact

solvimus GmbH
Ratsteichstr. 5
98693 Ilmenau
Germany
Phone: +49 3677 7613060
E-Mail: info@solvimus.de
www.solvimus.de

Sales:

Phone: +49 3677 7613066
E-Mail: sales@solvimus.de

Support:

Phone: +49 3677 7613065
E-Mail: support@solvimus.de

Further contacts can be found on our website at:
<https://www.solvimus.de/en/company/solvimus/>

A comprehensive description of the device is provided in the manual that can be accessed via the Help button on the configuration website of the device and can be downloaded free of charge and without registration from our homepage:
<https://www.solvimus.de/en/products/downloads-2/>

Our Quick Start Guide is also available upon request.

The solvimus GmbH works according to the principle of continuous improvement. The information given in this document is subject to change without prior notice and is provided without assertion, warranty or guarantee, including as to accuracy, completeness or fitness for a particular purpose. The statements in this document are not to be construed as a guarantee or assertion. This document is protected under copyright law.

