



DATA SHEET MUC.ONLY W

1. Product

MUC.only W, Art. No. 500391



2. Application

Data concentrator for readout of meters and data transmission to distant meter data management systems via NB-IoT (narrowband mobile radio communication).

3. Interfaces

wM-Bus

Compliant to EN 13757-4/-3/-7 and OMS (modes: S, T, C, C/T), max. 3 logical meters, internal antenna, frequency: 868 MHz (other frequencies upon request), Listen mode (automatic addition of meters), transparent mode, handling of keys, decryption of meters

NB-IoT (WAN)

Mobile radio: NB-IoT modem, LTE Cat-NB, internal antenna, card holder for micro SIM card, bands: LTE B1, B3, B5, B8, B20, B28

WLAN (WIFI)

Compliant to IEEE 802.11 b/g/n, centre frequency depending on channel: 2412-2484 MHz, internal antenna, function as access point

4. LED indicators

One LED each for Power, Readout, and WIFI access point

5. Software functions

The user interface of the software is available only in English.

Update of the firmware including integrity check and authentication.

Configuration

- Complete configuration via browser
- Export and import of the configuration including certificate and key files
- Update via the web page
- Logging function for error analysis

Data transmission to servers:

- MQTT (encrypted and unencrypted)

File format:

Freely configurable by Lua scripts (e. g. CSV, XML, JSON; upon request).

6. Processing unit

The processing unit is a microprocessor system:

- CPU: 32 bit LX7, up to 240 MHz clock frequency
- Memory: 320 kB RAM, 4 MB Flash
- Operating system: FreeRTOS

7. General properties

- Dimensions: 125 x 150 x 60 mm (W x H x D)
- Installation: wall mounting
- Mass: 580 g (with batteries)



8. Power supply

- 2 Lithium batteries 3.6 V, D cell
- Quiescent current: <100 nA

9. Environmental conditions

- Operation: 0..50 °C (daily average temperature); -20..70 °C (short-time)
- Transport and storage: max. 30 °C (recommended for optimum battery life)
- Air humidity: 0..95 %, non-condensing

10. Conformity and safety

- 2014/53/EU Radio Equipment Directive
- 2011/65/EU RoHS Directive (incl. amendment 2015/863)
- Protection class III (IEC 61140)
- Degree of protection IP67 (IEC 60529)

11. Scope of delivery

- MUC.only W
- 2 primary cells ER 34615J D, LiSOCl₂, 3.6 V, D cell, 19 Ah, manufacturer: Jauch Quartz GmbH, Germany
- Individual packaging

12. Contact

solvimus GmbH
Ratsteichstr. 5
98693 Ilmenau
Germany
Phone: +49 3677 7613060
E-Mail: info@solvimus.de
www.solvimus.de

Sales:

Phone: +49 3677 7613066
E-Mail: sales@solvimus.de

Support:

Phone: +49 3677 7613065
E-Mail: support@solvimus.de

Further contacts can be found on our website at:
<https://www.solvimus.de/en/homepage/>

The solvimus GmbH works according to the principle of continuous improvement. The information given in this document is subject to change without prior notice and is provided without assertion, warranty or guarantee, including as to accuracy, completeness or fitness for a particular purpose. The statements in this document are not to be construed as a guarantee or assertion. This document is protected under copyright law.